

CPA upload with CPA 4.0.8 or higher

Valves with IC2 controller

SW update over USB-Service port

Topic:

The CPA-SW is the Service-SW and is used for the communication over the service port. Valves (Controller) with CPA-SW before CPA 4.0.7 have no "Update Tool" integrated. Therefore it makes sense to load a newer version and update the CPA on the valves.

In this document it is described how to download CPA 4.0.8 or higher to a valve with CPA 4.0.0 ... 4.0.6.

Contents

1	CPA-SW used for IC2-Controller	2
1.1	Required Tools/SW	2
1.2	Where to find the CPA SW	2
1.3	Installation of CPA 4.0.8 (4.x.x)	3

1 CPA-SW used for IC2-Controller

CPA-SW-versions before CPA 4.0.7 had no function "Update Tool".
The latest version of the CPA-SW has enhanced functions like a SW-Upload function and other features. Therefore it makes sense to load the latest version of the CPA-SW.

 Make sure that the whole system is shut down before making a SW update
(no process in work)

 Loading wrong SW can lead to malfunctions and can destroy the valve/system

1.1 Required Tools/SW

PC or Laptop with windows (7 or higher)
Service cable (USB-A/B male/male)

SW which should be updated on the valve (controller)
➔ delivered by E-mail (eg file "xxxxxx.cpa" (897311.cpa = CPA 4.0.8))

Data/Documents from our homepage (see address/link below)

1.2 Where to find the CPA SW

 You find the actual version of the CPA on our Vatvalve homepage:

<http://www.vatvalve.com/business/global-services/informations-and-downloads/control-performance-analyzer>

CPA 3.x.x is used for IC-controllers (It's strictly forbidden to download CPA 4.x.x)

CPA 4.x.x is used for IC2-controllers

 Loading a wrong SW can lead to malfunctions and can destroy the valve/system


If you need additional information please contact VAT.

1.3 Installation of CPA 4.0.8 (4.x.x)



The installation is described for version 4.0.8

1. Please download CPA_v4.0.8.zip from our homepage (Executable Version for Windows)
2. Unpack the Zip file into a directory (eg CPA_v4.0.8)



3. Start CPA (no installation required)

Go to the directory where CPA_v4.0.8 was unpacked and start the file CPA4.




Ensure that PC and valve are connected (USB A/B male/male) and powered.

4. Go to "Update Tool"



The SW CPA_v4.0.8 is started on the PC


Activate the Local mode and go to "Update Tool"




5. Download the CPA-SW to the valve

Load the delivered file "xxxxxx.cpa" (delivered by Email !!)


Press load and go to the place where you stored the file "xxxxxx.cpa" (897311.cpa = CPA 4.0.8) and DoubleClick on it or drag&drop it in the Window "files"




Press "Start" to initialize the download to the valve



File will be downloaded (can need about 2 minutes)



Bytes downloaded and progress of download is shown
The download needs about 2 minutes



 Information that update was successful

Press "Close"

The loaded CPA-version is now updated on the valve.

Close the Program CPA

For further communication just connect the valve with the PC

 The CPA-SW will start automatically if a PC and the valve are connected over the service-cable.